

HEAVY-DUTY 75 W 2 m FM TRANSCEIVER

FT-2900R

The King of Mobile

- Massive Heatsink guarantees 75 Watts of Solid RF Power with No Cooling Fan Needed
- Loud 3 Watts of Audio Output for noisy environments
- Large 6 Digit Backlit LCD for excellent visibility
- 200 Memory Channels for serious users

75 WATTS




FT-2900R HEAVY-DUTY 75 W 2 m FM TRANSCEIVER

Yaesu's FT-2900R, the most ruggedly-built 2-meter amateur transceiver ever, provides 75 Watts of power along with Yaesu's renowned bullet-proof receiver front end. Direct keypad frequency entry, Alpha-Numeric Memory System, the high power output, and unsurpassed ergonomics make the FT-2900R an operator's dream come true!

Main Features

- Massive Heatsink guarantees 75 Watts of Solid RF Power with No Cooling Fan Needed
- Loud 3 Watts of Audio Output for noisy environments
- Large 6 Digit Backlit LCD for excellent visibility
- 200 Memory Channels for serious users
- Alpha-numeric Channel Display
- CTCSS and DCS Encode/Decode Built In
- Versatile Scanning Capability
- Smart Search™
- WiRES™ Internet Linking Access Feature
- MH-48A6J DTMF Direct Access Microphone
- Excellent Receiver Performance
- Wide/Narrow Deviation Selection
- RF-Level Squelch
- Interactive Programming Menu
- Supply Voltage Display
- Transmit Time-Out Timer (TOT)
- Automatic Power-Off (APO)
- Automatic Repeater Shift (ARS)
- 4-level Display Dimmer
- Dual Watch

RF Output Power Test Data (reference only)



Stable RF Output Power throughout the Bands

About this brochure: we have made this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time in equipment, optional accessories, specifications, model numbers, and availability. Precise frequency range may be different in some countries. Some accessories shown herein may not be available in some countries. Some information may have been updated since the time of printing; please check with your Authorized Yaesu Dealer for complete details.

YAESU VERTEX STANDARD CO., LTD.
4-8-8 Nakameguro, Meguro-ku, Tokyo 153-8644, Japan

For the latest Yaesu news, visit us on the Internet: <http://www.vxstd.com>

SPECIFICATIONS

General	
Frequency Ranges	136-174 MHz
Channel Step	5/10/12.5/15/20/25/50/100 kHz
Standard Repeater Shift	±600 kHz
Frequency Stability	Better than ±10 ppm -4° F to 140° F (-20° C to +60° C)
Modes of Emission	F2D, F3E
Antenna Impedance	50 Ohms, unbalanced
Supply Voltage	13.8 V DC ±15 %, negative ground
Current Consumption	RX: less than 0.7 A, less than 0.3 A (squelched) TX: 15 A(75 W)/ 9 A(30 W)/ 5 A(10 W)/4 A(5 W)
Operating Temperature Range	-4° F to +140° F (-20° C to +60° C)
Case Size(WxHxD)	6.3" x 2.0" x 7.3" (160 x 50 x 185 mm) (w/o knobs)
Weight	4.2 lb (1.9 kg)
Transmitter	
Output Power	75 W / 25W / 10W / 5W
Modulation Type	Variable Reactance
Maximum Deviation	±5 kHz / ±2.5 kHz
Spurious Radiation	Better than -60 dB
Microphone Impedance	2 kOhms
Receiver	
Circuit Type	Double Conversion Superheterodyne
IFs	21.7 MHz & 450 kHz
Sensitivity (for 12 dB SINAD)	Better than 0.4 µV
Selectivity(-6/-60 dB)	12 kHz / 28 kHz
IF Rejection	Better than 70 dB
Image Rejection	Better than 70 dB
Maximum AF Output	3 W into 4 Ohms @ 10 % THD

Specifications subject to change without notice or obligation.
Specifications guaranteed only within Amateur band.

Supplied Accessories

MH-48A6J DTMF Microphone
MMB-83 Mobile Mounting Bracket
DC cable

Accessories & Options

FP-1030A External Power Supply (25A)
MLS-100 External Speaker (12 W Peak Power)

VERTEX STANDARD <http://www.vertexstandard.com>

US Headquarters
10900 Walker Street, Cypress, CA 90630, U.S.A.

YAESU UK LTD. <http://www.yaesu.co.uk>
Unit 12, Sun Valley Business Park, Winnall Close
Winchester, Hampshire, SO23 0LB, U.K.

VERTEX STANDARD HK LTD. <http://www.vxstd.com.hk>

Unit 1306-1308, 13/F., Millennium City 2,
378 Kwun Tong Road, Kwun Tong, Kowloon, Hong Kong

VERTEX STANDARD AUSTRALIA PTY. LTD.

10 Wesley Court, Burwood East VIC 3151, Australia <http://www.vxstd.com.au>

